



CONDENSATE  
MANAGEMENT SYSTEMS

Tel: 01656 745552  
55 Park Street, Kenfig Hill, Bridgend, CF33 6DF  
www.royaleproducts.co.uk

## Condensate Pump Model CP5S

The CP5S condensate pump is designed specifically for use underneath refrigerated cabinets and accordingly should not be used for any other purpose.

### Operation:

The operation of the pump is controlled by two preset float switches. The pump is activated by the high level float switch and de-activated by the low level float switch. The float switches operate the pump via a power relay.

### Alarm Switch:

An additional float switch is available (as an extra) for alarm duty, for connection to an external monitor.

### Specifications:

<b>Dimensions:</b>	530 x 170 x 80mm
<b>Tank capacity:</b>	4 litres
<b>Construction:</b>	Formed, 18swg stainless steel
<b>Pump motor:</b>	Magnetic drive, regenerative pump mounted to an induction motor, rated 0.5A. Thermally protected.
<b>Pump duty:</b>	Maximum lift 6 metres
<b>Connections:</b>	1¼" drain - 10mm hose
<b>Level control:</b>	Dual preset float switches operating the pump via a power relay
<b>Voltage:</b>	230V

**Performance:** (Tested with clean cold water @20°C)

