



CONDENSATE  
MANAGEMENT SYSTEMS

Tel: 01656 745552  
55 Park Street, Kenfig Hill, Bridgend, CF33 6DF  
www.royaleproducts.co.uk

## Condensate Pump Model CP8H-RV

The CP8-RV condensate pump is designed specifically for use underneath refrigerated cabinets and accordingly should not be used for any other purpose.

### Operation:

The operation of the pump is controlled by two preset float switches. The pump is activated by the high level float switch and de-activated by the low level float switch. The float switches operate the pump via a power relay.

### Alarm Switch:

An additional float switch is available (as an extra) for alarm duty, for connection to an external monitor.

### Specifications:

<b>Dimensions:</b>	600 x 300 x 100mm
<b>Tank capacity:</b>	10 litres
<b>Construction:</b>	Formed, 18swg stainless steel
<b>Pump motor:</b>	Magnetic drive, twin centrifugal pumps mounted to a permanent capacitor induction motor, rated 0.6A. Thermally protected.
<b>Pump duty:</b>	Maximum lift 8 metres. Maximum flow volume 15 litres/minute
<b>Connections:</b>	1½" drain - 15mm hose
<b>Level control:</b>	Dual preset float switches operating the pump via a power relay
<b>Voltage:</b>	230V

**Performance:** (Tested with clean cold water @20°C)

